


GATE VALVES



Available in five sizes, three pressure ranges with screwed end, butt weld or flanged connections.

100% interchangable with Oteco - model 72, Cameron - flex seal

1	Bit	rio .	1	10	2	17			-	135				
A	.7%	te y	F5.		100	1000				[3]	100			
. 6	201	70074	1000	16.5	365	.01%			+01.74	100				
1,850	1,170.	1000	1751	DAME.	A34.	11895			# 1 T.	Poor.				
.0	98	146	1970	.955x	Jith.	JIPs.			100		2.1			
	14	146	950	1856	34	At:			T III		1.			
-5-	_	40		18%		100			1	-		1		
	1	127.7	100	356		254			-	4				
200		1200	han.	1		4			j-m-		40			
Sec.		40		196	148	210			***	No Filt				
	3000 pt/ W.F							3000 pai W.F						
2	JY.	Gr.	150	3,950	100	-	7	-201	1263	100	Spo	100		
3	Sec	179.3	75	55	344	790	7	Sec-	156	Sec.	PRO.	Tot.	11/4	
1	Sec.	Fig.	Sec	14	1	Par.	1.5	the .	No.	200	Has	Due.	15	
		100		-	41	100	-	-	100	-	100		11/2	
	-	157%	CO.	140.	.79	180.	PUA.		100.	.90.00		30,11	-	
DEC.	250	1/2/2/2	Law.	10550	46	.7951	\$11210	The .	JUO.	1000	3334	1990	177.	
	4410an	10%	285.50	Dire	30%	34%	100	10.4	Maria	414	-	(5.5a)	in	
8.00	#HICTOR	DEPACT	380	28	915.1	ERGE	20000	H'm	High total	<u>an</u>	200	100	160	
		B 10		450		10.50			100		405	-	ЫK	
		11160		250		1980	F ACT	19/44			POC C	270	-	
19	35	1	- 8		+		- 4	2	1.	15	1.1		100	
Shoph.	19	11-5	100	199	2296	100	900	84	tue:	19617	200	216	1 kir	
		MITTE A	alaba.	-		-	-	and and in	-	Section			_	
-	restal.													



INTERNATIONAL OIL FIELD SERVICES b.v.

Industrieweg 39 7761 PV Schoonebeek Fax: 00-31-524-533 475

Tel.: 00-31-524-533 477

